

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/045749 A1

(51) International Patent Classification⁷: **B01D 63/00,**
61/00

(21) International Application Number:
PCT/US2003/036427

(22) International Filing Date:
12 November 2003 (12.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/426,768 14 November 2002 (14.11.2002) US

(71) Applicant and

(72) Inventor: **GRAY, Buddy, Don** [US/US]; 121 Bee Springs
Road, Dellrose, TN 38453 (US).

(74) Agents: **TARLETON, Russell, E.** et al.; Seed Intellectual
Property Law Group PLLC, Suite 6300, 701 Fifth Avenue,
Seattle, WA 98104-7092 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: PROPORTIONING, REGENERATIVE, ROTARY PUMP

(57) Abstract: A pump system for tangential flow or crossflow liquid filtration systems, such as reverse osmosis, nano, and micro filtration systems, that independently fixes the fraction of product water produced for each stage and recovers a fraction of the energy normally lost in rejected waste streams. The pump is of the rotary positive-displacement type and fixes the percent recovery of the overall system by establishing set ratios through the use of differing displacements of the various pump and motor stages, per unit of time, between the feed water inlet, product water outlet, and reject water outlet volume of each stage of the filtration system while using the same ratio setting components to recover the energy normally expelled along with the reject, or concentrate water. The pump system, while initially developed for use in water processing, can find equal or greater use in processing of fluid streams other than water and in processes other than filtration or reverse osmosis.



WO 2004/045749 A1